


4 mm • Programming Data

DEFINITIONS

- » **DCX:** maximum cutting diameter
- » **DC:** effective cutter diameter
- » **KAPR:** cutting edge angle
- » **APMX:** maximum depth of cut
- » **REEQ:** program radius
- » **BS:** axial wiper length
- » **BS2:** radial wiper length



Part Number	DCX Cutting Dia. Max.	DC Cutting Dia.
15G1B-03006T6R01	0.375	0.167
15G1B-03015R8R01	0.375	0.167
15G1B-05007T8R01	0.500	0.291
15G1B-05007X4R01	0.500	0.291
15G1B-05015S4R01	0.500	0.291
15G1B-06008TRR01	0.625	0.415
15G1B-06010X5R01	0.625	0.415
15G1B-06015S6R01	0.625	0.415
15G1B-07010TSR01	0.750	0.540
15G1B-07010X6R01	0.750	0.540
15G1B-07015S7R01	0.750	0.540

4 mm • Programming Tips

- » The shape of the insert nose can be approximated by programming as-if the insert had a **.042"** corner radius (REEQ). The difference will result in an unmachined area that's approximately **.013"** deep.
- » The recommendations for cutting speed, chip-thickness grade, and insert geometry are starting recommendations and should be optimized based on the type and rate of edge failure.
- » The **Machining Calculator App**, on Ingersoll's website, is another resource for estimating and optimizing parameters. There are additional inputs like the radial width of cut and the effective rake angle can be included into the estimates.

