



### MILLING - INDEXABLE

#### Cutter Series (Angle x Depth of Cut)

- DN5G DN6G (45° x 0.165")
- DG6G (20° x .070")
- DN5K DN6K (45° x 0.235")
- DG6K (20° x 0.100")

#### Insert Series

- SQGU11
- SQGU14

#### Diameter Range

1.50-8.00" (40-200 mm)

#### Lead Angles

- 45°
- 20° (hi-feed)

#### Materials

- Steel
- Iron

# DIPOSQUAD<sup>TM</sup>

### 45° and Hi-Feed Face Mills that share the same High-Strength, 8-Edge Insert

- » Extreme geometry enjoys heavy feed rates and promotes efficient chip evacuation.
- » Offered with 2 insert IC sizes for depth-of-cut and density diversity.
- » Integrated wiper flats produce 32-63 Ra finishes.



11 mm



14 mm



20°



45°



See it in  
action! »



**WINSPEED<sup>TM</sup>**  
ADVANCED MACHINING


[ingersoll-imc.com](http://ingersoll-imc.com)




## Features & Benefits

- Economical double-sided 8-corner insert
- Two lead angle cutters for roughing and high-feed machining


### 45° cutters: deep depth of cut for roughing




### 20° cutters: for high feed milling




- Wiper edge for excellent surface roughness  
**Note:** good visual roughness requires feed rate adjustment
- Reinforced edge optimized for high feed machining



- High negative radial rake angle and high positive axial rake angle




- Excellent chip evacuation due to reduced chip volume
- Enhanced body rigidity for excellent machining performance under harsh cutting conditions
- Fine pitch cutter maximizes productivity




Conventional cutter	DiPosQuadF cutter	
	Normal pitch	Fine pitch
<p>Reduced body rigidity</p> <p>Reduced body rigidity due to the wider space for insert clamping and chip evacuation</p>	<p>Improved body rigidity</p> <p>Improved body rigidity and ideal chip evacuation in the narrowest space</p>	<p>Larger number of teeth for higher productivity</p>

Face Lead Angle Channel




## 11 mm • Series DN5G, DN6G

### 45° FACE MILL




Part Number	DC Cutting Diameter	DCX Cutting Diameter Max.	OAL Overall Length	ZEFF Eff. Teeth	BD Body Diameter	DCON Bore Diameter	KWW Keyway	CSP Coolant
<b>INCH</b>								
DN6G-15R01	1.500	1.93	1.570	4	1.97	0.5000	0.250	Yes
DN5G-15R01	1.500	1.93	1.570	6	1.97	0.5000	0.250	Yes
DN6G-20R01	2.000	2.43	1.750	6	2.47	0.7500	0.312	Yes
DN5G-20R01	2.000	2.43	1.750	8	2.47	0.7500	0.312	Yes
DN6G-25R01	2.500	2.93	1.750	7	2.97	1.0000	0.375	Yes
DN5G-25R01	2.500	2.93	1.750	10	2.97	1.0000	0.375	Yes
DN6G-30R01	3.000	3.43	1.750	8	3.47	1.0000	0.375	Yes
DN5G-30R01	3.000	3.43	1.750	12	3.47	1.0000	0.375	Yes
DN6G-40R01	4.000	4.43	2.375	9	4.47	1.5000	0.625	Yes
DN5G-40R01	4.000	4.43	2.375	14	4.47	1.5000	0.625	Yes
DN6G-50R01	5.000	5.43	2.375	12	5.47	1.5000	0.625	Yes
DN5G-50R01	5.000	5.43	2.375	18	5.47	1.5000	0.625	Yes
DN6G-60R01	6.000	6.43	2.375	16	6.47	1.5000	0.625	No
DN5G-60R01	6.000	6.43	2.375	24	6.47	1.5000	0.625	No
<b>METRIC</b>								
DN5G040R00	40.00 mm	51.0 mm	40.00 mm	6	52.0 mm	16.000 mm	8.40 mm	Yes
DN6G040R00	40.00 mm	51.0 mm	40.00 mm	4	52.0 mm	16.000 mm	8.40 mm	Yes
DN5G050R00	50.00 mm	61.0 mm	40.00 mm	8	62.0 mm	22.000 mm	10.40 mm	Yes
DN6G050R00	50.00 mm	61.0 mm	40.00 mm	6	62.0 mm	22.000 mm	10.40 mm	Yes
DN5G063R00	63.00 mm	74.0 mm	50.00 mm	10	75.0 mm	22.000 mm	10.40 mm	Yes
DN6G063R00	63.00 mm	74.0 mm	50.00 mm	7	75.0 mm	22.000 mm	10.40 mm	Yes
DN5G080R00	80.00 mm	91.0 mm	50.00 mm	12	92.0 mm	27.000 mm	12.40 mm	Yes
DN6G080R00	80.00 mm	91.0 mm	50.00 mm	8	92.0 mm	27.000 mm	12.40 mm	Yes
DN5G100R00	100.00 mm	111.0 mm	50.00 mm	14	112.0 mm	32.000 mm	14.40 mm	Yes
DN6G100R00	100.00 mm	111.0 mm	50.00 mm	9	112.0 mm	32.000 mm	14.40 mm	Yes
DN5G125R00	125.00 mm	136.0 mm	63.00 mm	18	137.0 mm	40.000 mm	16.40 mm	Yes
DN6G125R00	125.00 mm	136.0 mm	63.00 mm	12	137.0 mm	40.000 mm	16.40 mm	Yes
DN5G160R00	160.00 mm	171.0 mm	63.00 mm	24	172.0 mm	40.000 mm	16.40 mm	No
DN6G160R00	160.00 mm	171.0 mm	63.00 mm	16	172.0 mm	40.000 mm	16.40 mm	No



# 11 mm • Series DG6G

## 20° FACE MILL • HI-FEED







Part Number	DC Cutting Diameter	DCX Cutting Diameter Max.	OAL Overall Length	ZEFF Eff. Teeth	DCON Bore Diameter	KWW Keyway	CSP Coolant
<b>INCH</b>							
DG6G-20R01	2.000	2.53	1.570	4	0.7500	0.312	Yes
DG6G-25R01	2.500	3.03	1.750	5	1.0000	0.375	Yes
DG6G-30R01	3.000	3.53	1.750	6	1.0000	0.375	Yes
DG6G-40R01	4.000	4.53	2.375	8	1.5000	0.625	Yes
<b>METRIC</b>							
DG6G050R00	50.00 mm	63.50 mm	40.00 mm	4	22.00 mm	10.40 mm	Yes
DG6G063R00	63.00 mm	76.50 mm	50.00 mm	5	22.00 mm	10.40 mm	Yes
DG6G080R00	80.00 mm	93.50 mm	50.00 mm	6	27.00 mm	12.40 mm	Yes
DG6G100R00	100.00 mm	113.50 mm	50.00 mm	8	32.00 mm	14.40 mm	Yes




## 11 mm • Inserts

### FOR SERIES DN5G, DN6G, AND DG6G

#### SQGU11\_M












#### SQGU11\_ML



Part Number	Application	BS Wiper Length	BS2 Wiper Length	IC Inscribed Circle Dia.	S Thickness	NOI Number of Indexes	IH Insert Hand	Grade				
								IN2036	IN2505	IN2510	IN2530	IN6537
SQGU1105ANR-M	Multi-Purpose	0.075	0.039	0.44	0.248	8	Right		•	•		•
SQGU1105ANR-ML	SS / Hi-Temp / Ti	0.075	0.039	0.44	0.248	8	Right	•	•		•	


## 11 mm • Hardware

Part Number					Optional			
								
	Screw	Driver Handle	Torx Driver Blade	Retention Bolt	Coolant Retention Bolt	Torque Driver Handle	Preset Torque Adapter	Torque Driver Bit
<b>INCH</b>								
DN6G-15R01	SM40-115-00	DS-A00T	DS-T156B	SD-04-46	-	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN5G-15R01	SM40-115-00	DS-A00T	DS-T156B	SD-04-46	-	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN6G-20R01	SM40-115-00	DS-A00T	DS-T156B	SD-06-47	SD-06-A6	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN5G-20R01	SM40-115-00	DS-A00T	DS-T156B	SD-06-47	SD-06-A6	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN6G-25R01	SM40-115-00	DS-A00T	DS-T156B	SD-08-47	SD-08-C9	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN5G-25R01	SM40-115-00	DS-A00T	DS-T156B	SD-08-47	SD-08-C9	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN6G-30R01	SM40-115-00	DS-A00T	DS-T156B	SD-08-47	SD-08-C9	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN5G-30R01	SM40-115-00	DS-A00T	DS-T156B	SD-08-47	SD-08-C9	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN6G-40R01	SM40-115-00	DS-A00T	DS-T156B	SD-12-82	SD-12-99	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN5G-40R01	SM40-115-00	DS-A00T	DS-T156B	SD-12-82	SD-12-99	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN6G-50R01	SM40-115-00	DS-A00T	DS-T156B	SD-12-82	SD-12-99	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN5G-50R01	SM40-115-00	DS-A00T	DS-T156B	SD-12-82	SD-12-99	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN6G-60R01	SM40-115-00	DS-A00T	DS-T156B	-	-	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN5G-60R01	SM40-115-00	DS-A00T	DS-T156B	-	-	DS-A00-.25-T	DT-35-.25	DS-T15B1
DG6G-20R01	SM40-115-00	DS-A00T	DS-T156B	SD-06-47	SD-06-A6	DS-A00-.25-T	DT-35-.25	DS-T15B1
DG6G-25R01	SM40-115-00	DS-A00T	DS-T156B	SD-08-47	SD-08-C9	DS-A00-.25-T	DT-35-.25	DS-T15B1
DG6G-30R01	SM40-115-00	DS-A00T	DS-T156B	SD-08-47	SD-08-C9	DS-A00-.25-T	DT-35-.25	DS-T15B1
DG6G-40R01	SM40-115-00	DS-A00T	DS-T156B	SD-12-82	SD-12-99	DS-A00-.25-T	DT-35-.25	DS-T15B1
<b>METRIC</b>								
DN5G040R00	SM40-115-00	DS-A00T	DS-T156B	SHM8X1.25X25	SHM8X1.25X25-C	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN6G040R00	SM40-115-00	DS-A00T	DS-T156B	SHM8X1.25X25	SHM8X1.25X25-C	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN5G050R00	SM40-115-00	DS-A00T	DS-T156B	SHLM10X1.5X25	SHLM10X1.5X25-C	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN6G050R00	SM40-115-00	DS-A00T	DS-T156B	SHLM10X1.5X25	SHLM10X1.5X25-C	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN5G063R00	SM40-115-00	DS-A00T	DS-T156B	SHM10X1.5X30	SHM10X1.5X30-C	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN6G063R00	SM40-115-00	DS-A00T	DS-T156B	SHM10X1.5X30	SHM10X1.5X30-C	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN5G080R00	SM40-115-00	DS-A00T	DS-T156B	SHLM12X1.75X30	SHLM12X1.75X30-C	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN6G080R00	SM40-115-00	DS-A00T	DS-T156B	SHLM12X1.75X30	SHLM12X1.75X30-C	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN5G100R00	SM40-115-00	DS-A00T	DS-T156B	SHLM16X2X35	SHLM16X2X35-C	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN6G100R00	SM40-115-00	DS-A00T	DS-T156B	SHLM16X2X35	SHLM16X2X35-C	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN5G125R00	SM40-115-00	DS-A00T	DS-T156B	SHM20X2.5X40	SHM20X2.5X40-C	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN6G125R00	SM40-115-00	DS-A00T	DS-T156B	SHM20X2.5X40	SHM20X2.5X40-C	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN5G160R00	SM40-115-00	DS-A00T	DS-T156B	-	-	DS-A00-.25-T	DT-35-.25	DS-T15B1
DN6G160R00	SM40-115-00	DS-A00T	DS-T156B	-	-	DS-A00-.25-T	DT-35-.25	DS-T15B1
DG6G050R00	SM40-115-00	DS-A00T	DS-T156B	SHM10X1.5X30	SHM10X1.5X30-C	DS-A00-.25-T	DT-35-.25	DS-T15B1
DG6G063R00	SM40-115-00	DS-A00T	DS-T156B	SHM10X1.5X30	SHM10X1.5X30-C	DS-A00-.25-T	DT-35-.25	DS-T15B1
DG6G080R00	SM40-115-00	DS-A00T	DS-T156B	SHM12X1.75X35	SHM12X1.75X35-C	DS-A00-.25-T	DT-35-.25	DS-T15B1
DG6G100R00	SM40-115-00	DS-A00T	DS-T156B	SHLM16X2X35	SHLM16X2X35-C	DS-A00-.25-T	DT-35-.25	DS-T15B1




## 14 mm • Series DN5K, DN6K

### 45° FACE MILL




Part Number	DC Cutting Dia.	DCX Cutting Dia. Max.	OAL Overall Length	ZEFF Eff. Teeth	BD Body Dia.	DCON Bore Dia.	KWW Keyway	DBC Bolt Circle Dia.	CSP Coolant Dia.
<b>INCH</b>									
DN6K-20R01	2.000	2.61	1.750	4	2.67	0.7500	0.312	-	Yes
DN5K-20R01	2.000	2.61	1.750	6	2.67	0.7500	0.312	-	Yes
DN6K-25R01	2.500	3.11	1.750	6	3.17	1.0000	0.375	-	Yes
DN5K-25R01	2.500	3.11	1.750	8	3.17	1.0000	0.375	-	Yes
DN6K-30R01	3.000	3.61	1.750	7	3.67	1.0000	0.375	-	Yes
DN5K-30R01	3.000	3.61	1.750	10	3.67	1.0000	0.375	-	Yes
DN6K-40R01	4.000	4.61	2.375	8	4.67	1.5000	0.625	-	Yes
DN5K-40R01	4.000	4.61	2.375	12	4.67	1.5000	0.625	-	Yes
DN6K-50R01	5.000	5.61	2.375	10	5.67	1.5000	0.625	-	Yes
DN5K-50R01	5.000	5.61	2.375	16	5.67	1.5000	0.625	-	Yes
DN6K-60R01	6.000	6.61	2.375	12	6.67	1.5000	0.625	-	No
DN5K-60R01	6.000	6.61	2.375	20	6.67	1.5000	0.625	-	No
DN6K-80R01	8.000	8.61	2.375	18	8.67	2.5000	1.000	4.00	No
DN5K-80R01	8.000	8.61	2.375	26	8.67	2.5000	1.000	4.00	No
<b>METRIC</b>									
DN6K050R00	50.00 mm	65.5 mm	40.00 mm	4	67.0 mm	22.00 mm	10.40 mm	-	Yes
DN5K050R00	50.00 mm	65.5 mm	40.00 mm	6	67.0 mm	22.00 mm	10.40 mm	-	Yes
DN6K063R00	63.00 mm	78.5 mm	50.00 mm	6	80.0 mm	22.00 mm	10.40 mm	-	Yes
DN5K063R00	63.00 mm	78.5 mm	50.00 mm	8	80.0 mm	22.00 mm	10.40 mm	-	Yes
DN6K080R00	80.00 mm	95.5 mm	50.00 mm	7	97.0 mm	27.00 mm	12.40 mm	-	Yes
DN5K080R00	80.00 mm	95.5 mm	50.00 mm	10	97.0 mm	27.00 mm	12.40 mm	-	Yes
DN6K100R00	100.00 mm	115.5 mm	50.00 mm	8	117.0 mm	32.00 mm	14.40 mm	-	Yes
DN5K100R00	100.00 mm	115.5 mm	50.00 mm	12	117.0 mm	32.00 mm	14.40 mm	-	Yes
DN6K125R00	125.00 mm	140.5 mm	63.00 mm	10	142.0 mm	40.00 mm	16.40 mm	-	Yes
DN5K125R00	125.00 mm	140.5 mm	63.00 mm	16	142.0 mm	40.00 mm	16.40 mm	-	Yes
DN6K160R00	160.00 mm	175.5 mm	63.00 mm	12	177.0 mm	40.00 mm	16.40 mm	-	No
DN5K160R00	160.00 mm	175.5 mm	63.00 mm	20	177.0 mm	40.00 mm	16.40 mm	-	No
DN6K200R00	200.00 mm	215.5 mm	63.00 mm	18	217.0 mm	60.00 mm	25.70 mm	101.6 mm	No
DN5K200R00	200.00 mm	215.5 mm	63.00 mm	26	217.0 mm	60.00 mm	25.70 mm	101.6 mm	No





## 14 mm • Series DG6K

### 20° FACE MILL • HI-FEED







Part Number	DC Cutting Diameter	DCX Cutting Diameter Max.	OAL Overall Length	ZEFF Eff. Teeth	DCON Bore Diameter	KWW Keyway	CSP Coolant
<b>INCH</b>							
DG6K-25R01	2.500	3.19	1.750	5	1.00	0.375	Yes
DG6K-30R01	3.000	3.69	1.750	6	1.00	0.375	Yes
DG6K-40R01	4.000	4.69	2.375	7	1.50	0.625	Yes
DG6K-60R01	6.000	6.69	2.375	8	1.50	0.625	No
<b>METRIC</b>							
DG6K063R00	63.00 mm	80.6 mm	50.00 mm	5	22.00 mm	10.40 mm	Yes
DG6K080R00	80.00 mm	97.6 mm	50.00 mm	6	27.00 mm	12.40 mm	Yes
DG6K100R00	100.00 mm	117.5 mm	50.00 mm	7	32.00 mm	14.40 mm	Yes
DG6K125R00	125.00 mm	142.5 mm	63.00 mm	8	40.00 mm	16.40 mm	Yes




## 14 mm • Inserts

### FOR SERIES DN5K, DN6K, AND DG6K

#### SQGU14\_M











#### SQGU14\_ML




Part Number	Application	BS Wiper Length	BS2 Wiper Length	IC Inscribed Circle Dia.	S Thickness	NOI Number of Indexes	IH Insert Hand	Grade				
								IN2036	IN2505	IN2510	IN2530	IN6537
SQGU1406ANR-M	Multi-Purpose	0.079	0.063	0.57	0.307	8	Right		•	•		•
SQGU1406ANR-ML	SS / Hi-Temp / Ti	0.079	0.063	0.57	0.307	8	Right	•	•		•	

## 14 mm • Hardware

Part Number					Optional			
								
INCH								
DN6K-20R01	SM50-130-R0	DS-A00T	DS-T206B	SD-06-47	SD-06-A6	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN5K-20R01	SM50-130-R0	DS-A00T	DS-T206B	SD-06-47	SD-06-A6	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN6K-25R01	SM50-130-R0	DS-A00T	DS-T206B	SD-08-47	SD-08-C9	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN5K-25R01	SM50-130-R0	DS-A00T	DS-T206B	SD-08-47	SD-08-C9	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN6K-30R01	SM50-130-R0	DS-A00T	DS-T206B	SD-08-47	SD-08-C9	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN5K-30R01	SM50-130-R0	DS-A00T	DS-T206B	SD-08-47	SD-08-C9	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN6K-40R01	SM50-130-R0	DS-A00T	DS-T206B	SD-12-82	SD-12-99	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN5K-40R01	SM50-130-R0	DS-A00T	DS-T206B	SD-12-82	SD-12-99	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN6K-50R01	SM50-130-R0	DS-A00T	DS-T206B	SD-12-82	SD-12-99	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN5K-50R01	SM50-130-R0	DS-A00T	DS-T206B	SD-12-82	SD-12-99	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN6K-60R01	SM50-130-R0	DS-A00T	DS-T206B	-	-	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN5K-60R01	SM50-130-R0	DS-A00T	DS-T206B	-	-	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN6K-80R01	SM50-130-R0	DS-A00T	DS-T206B	-	-	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN5K-80R01	SM50-130-R0	DS-A00T	DS-T206B	-	-	DS-A00-.25-T	DT-44-.25	DS-T20B1
DG6K-25R01	SM50-130-R0	DS-A00T	DS-T206B	SD-08-47	SD-08-C9	DS-A00-.25-T	DT-44-.25	DS-T20B1
DG6K-30R01	SM50-130-R0	DS-A00T	DS-T206B	SD-08-47	SD-08-C9	DS-A00-.25-T	DT-44-.25	DS-T20B1
DG6K-40R01	SM50-130-R0	DS-A00T	DS-T206B	SD-12-82	SD-12-99	DS-A00-.25-T	DT-44-.25	DS-T20B1
DG6K-60R01	SM50-130-R0	DS-A00T	DS-T206B	-	-	DS-A00-.25-T	DT-44-.25	DS-T20B1
METRIC								
DN6K050R00	SM50-130-R0	DS-A00T	DS-T206B	SHLM10X1.5X25	SHLM10X1.5X25-C	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN5K050R00	SM50-130-R0	DS-A00T	DS-T206B	SHLM10X1.5X25	SHLM10X1.5X25-C	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN6K063R00	SM50-130-R0	DS-A00T	DS-T206B	SHM10X1.5X30	SHM10X1.5X30-C	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN5K063R00	SM50-130-R0	DS-A00T	DS-T206B	SHM10X1.5X30	SHM10X1.5X30-C	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN6K080R00	SM50-130-R0	DS-A00T	DS-T206B	SHLM12X1.75X30	SHLM12X1.75X30-C	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN5K080R00	SM50-130-R0	DS-A00T	DS-T206B	SHLM12X1.75X30	SHLM12X1.75X30-C	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN6K100R00	SM50-130-R0	DS-A00T	DS-T206B	SHLM16X2X35	SHLM16X2X35-C	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN5K100R00	SM50-130-R0	DS-A00T	DS-T206B	SHLM16X2X35	SHLM16X2X35-C	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN6K125R00	SM50-130-R0	DS-A00T	DS-T206B	SHM20X2.5X40	SHM20X2.5X40-C	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN5K125R00	SM50-130-R0	DS-A00T	DS-T206B	SHM20X2.5X40	SHM20X2.5X40-C	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN6K160R00	SM50-130-R0	DS-A00T	DS-T206B	-	-	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN5K160R00	SM50-130-R0	DS-A00T	DS-T206B	-	-	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN6K200R00	SM50-130-R0	DS-A00T	DS-T206B	-	-	DS-A00-.25-T	DT-44-.25	DS-T20B1
DN5K200R00	SM50-130-R0	DS-A00T	DS-T206B	-	-	DS-A00-.25-T	DT-44-.25	DS-T20B1
DG6K063R00	SM50-130-R0	DS-A00T	DS-T206B	SHM10X1.5X30	SHM10X1.5X30-C	DS-A00-.25-T	DT-44-.25	DS-T20B1
DG6K080R00	SM50-130-R0	DS-A00T	DS-T206B	SHM12X1.75X35	SHM12X1.75X35-C	DS-A00-.25-T	DT-44-.25	DS-T20B1
DG6K100R00	SM50-130-R0	DS-A00T	DS-T206B	SHLM16X2X35	SHLM16X2X35-C	DS-A00-.25-T	DT-44-.25	DS-T20B1
DG6K125R00	SM50-130-R0	DS-A00T	DS-T206B	SHM20X2.5X40	SHM20X2.5X40-C	DS-A00-.25-T	DT-44-.25	DS-T20B1



## 11 mm (45°) • Operating Guidelines



ISO	Materials			Vc Cutting Speed SFM	fz* Feed/Tooth (inch)	Harder «-----» Tougher					Coolant
	Material Group #VDI 3323	Type	Examples			IN2510	IN2505	IN2530	IN2036	IN6537	
<b>P</b>	1-5	Non-Alloy Steel	1018, A36, 1045, A572, 1070	400-1000	.005-.013						No
	6-9	Low-Alloy Steel	4140, 4340, P20, 8620, 300M	350-700		3	2		1		
	10-11	High-Alloy Steel	H13, A2, D2, M2, T1	300-600							
<b>M</b>	12 - 13	Stainless Steel (Ferritic & Martensitic)	410, 416, 440	400-700	.005-.010		3	2	1		May not be required at high speeds
	14	Stainless Steel (Austenitic)	303, 304, 316, 15-5, 17-4	300-600							
<b>K</b>	15-16	Gray Cast Iron	CLS. 20, 30, 45	500-1000	.005-.013	1	2			3	No
	17-18	Nodular Cast Iron	60-40-18, 100-70-03	400-800							
<b>S</b>	31 - 35	High-Temp Alloys	Inconel, Hastelloy, Nimonic, Monel	75-120	.005-.010		3	2	1		Yes
	36 - 37	Titanium Alloys	6Al-4V, 5Al-5Mo-5V-3Cr	100-150			2	3	1		

Note: Feed and speed recommendations are starting operating parameters. They are only guidelines from which further optimization should take place. Operating parameters are influenced by many machining variables. These variables may cause for reductions in feeds and speed or dramatic increases. Additionally, DOC and WOC may need to be revised to optimize the tools performance.


## 11 mm (20°) • Operating Guidelines



ISO	Materials			Vc Cutting Speed SFM	fz* Feed/ Tooth (inch) <b>Hi-Feed</b>	fz* Feed/ Tooth (inch) <b>Plunge</b>	Harder «-----» Tougher					Coolant
	Material Group #VDI 3323	Type	Examples				IN2510	IN2505	IN2530	IN2036	IN6537	
<b>P</b>	1-5	Non-Alloy Steel	1018, A36, 1045, A572, 1070	400-1000	.012-.065	.004-.012	3	2	1	No		
	6-9	Low-Alloy Steel	4140, 4340, P20, 8620, 300M	350-700								
	10-11	High-Alloy Steel	H13, A2, D2, M2, T1	300-600								
<b>M</b>	12 - 13	Stainless Steel (Ferritic & Martensitic)	410, 416, 440	400-700	.012-.060	.004-.010	3	2	1	May not be required at high speeds		
	14	Stainless Steel (Austenitic)	303, 304, 316, 15-5, 17-4	300-600								
<b>K</b>	15-16	Gray Cast Iron	CLS. 20, 30, 45	500-1000	.015-.075	.004-.013	1	2	3	No		
	17-18	Nodular Cast Iron	60-40-18, 100-70-03	400-800								
<b>S</b>	31 - 35	High-Temp Alloys	Inconel, Hastelloy, Nimonic, Monel	75-120	.012-.050	.004-.010	3	2	1	Yes		
	36 - 37	Titanium Alloys	6Al-4V, 5Al-5Mo-5V-3Cr	100-150							2	3

Note: Feed and speed recommendations are starting operating parameters. They are only guidelines from which further optimization should take place. Operating parameters are influenced by many machining variables. These variables may cause for reductions in feeds and speed or dramatic increases. Additionally, DOC and WOC may need to be revised to optimize the tools performance.



## 14 mm (45°) • Operating Guidelines



ISO	Materials			Vc Cutting Speed SFM	fz* Feed/Tooth (inch)	Harder «-----» Tougher					Coolant
	Material Group #VDI 3323	Type	Examples			IN2510	IN2505	IN2530	IN2036	IN6537	
<b>P</b>	1-5	Non-Alloy Steel	1018, A36, 1045, A572, 1070	400-1000	.005-.016						No
	6-9	Low-Alloy Steel	4140, 4340, P20, 8620, 300M	350-700		3	2		1		
	10-11	High-Alloy Steel	H13, A2, D2, M2, T1	300-600							
<b>M</b>	12 - 13	Stainless Steel (Ferritic & Martensitic)	410, 416, 440	400-700	.005-.010		3	2	1		May not be required at high speeds
	14	Stainless Steel (Austenitic)	303, 304, 316, 15-5, 17-4	300-600							
<b>K</b>	15-16	Gray Cast Iron	CLS. 20, 30, 45	500-1000	.005-.016	1	2			3	No
	17-18	Nodular Cast Iron	60-40-18, 100-70-03	400-800							
<b>S</b>	31 - 35	High-Temp Alloys	Inconel, Hastelloy, Nimonic, Monel	75-120	.005-.010		3	2	1		Yes
	36 - 37	Titanium Alloys	6Al-4V, 5Al-5Mo-5V-3Cr	100-150			2	3	1		

Note: Feed and speed recommendations are starting operating parameters. They are only guidelines from which further optimization should take place. Operating parameters are influenced by many machining variables. These variables may cause for reductions in feeds and speed or dramatic increases. Additionally, DOC and WOC may need to be revised to optimize the tools performance.

## 14 mm (20°) • Operating Guidelines



ISO	Materials			Vc Cutting Speed SFM	fz* Feed/ Tooth (inch) <b>Hi-Feed</b>	fz* Feed/ Tooth (inch) <b>Plunge</b>	Harder «-----» Tougher					Coolant
	Material Group #VDI 3323	Type	Examples				IN2510	IN2505	IN2530	IN2036	IN6537	
<b>P</b>	1-5	Non-Alloy Steel	1018, A36, 1045, A572, 1070	400-1000	.015-.080	.004-.015	3	2	1	No		
	6-9	Low-Alloy Steel	4140, 4340, P20, 8620, 300M	350-700								
	10-11	High-Alloy Steel	H13, A2, D2, M2, T1	300-600								
<b>M</b>	12 - 13	Stainless Steel (Ferritic & Martensitic)	410, 416, 440	400-700	.012-.065	.004-.012	3	2	1	May not be required at high speeds		
	14	Stainless Steel (Austenitic)	303, 304, 316, 15-5, 17-4	300-600								
<b>K</b>	15-16	Gray Cast Iron	CLS. 20, 30, 45	500-1000	.015-.090	.004-.016	1	2	3	No		
	17-18	Nodular Cast Iron	60-40-18, 100-70-03	400-800								
<b>S</b>	31 - 35	High-Temp Alloys	Inconel, Hastelloy, Nimonic, Monel	75-120	.012-.055	.004-.012	3	2	1	Yes		
	36 - 37	Titanium Alloys	6Al-4V, 5Al-5Mo-5V-3Cr	100-150							2	3

Note: Feed and speed recommendations are starting operating parameters. They are only guidelines from which further optimization should take place. Operating parameters are influenced by many machining variables. These variables may cause for reductions in feeds and speed or dramatic increases. Additionally, DOC and WOC may need to be revised to optimize the tools performance.