

Operating Guidelines - 5xD

Materials				Condition	Tensile Strength (N/mm2)	HB Hardness	Vc Cutting Speed SFM	IPR Cutting Diameter (in/rev)													
ISO	Mtl Group No.	Type						3.0-6.0 mm (.118-.235")	6.0-9.0 mm (.236-.353")	9.0-12.0 mm (.354-.471")	12.0-16.0 mm (.472-.629")	16.0-19.05 mm (.630-.749")	19.05-20.0 mm (.750-.787")								
P	1	Non alloy steel and cast steel free cutting steel	< 0.25 %C	Annealed	420	125	375	.0030 - .0050	.0050 - .0075	.0075 - .0100	.0100 - .0130	.0130 - .0153	.0153 - .0160								
	2		>= 0.25 %C	Annealed	650	190															
	3		< 0.55 %C	Quenched and Tempered	850	250															
	4		>= 0.55 %C	Annealed	750	220															
	5		> 0.55 %C	Quenched and Tempered	1000	300															
	6	Low alloy steel and cast steel (less than 5% of alloying elements)			Annealed	600								200	275	.0030 - .0050	.0050 - .0075	.0075 - .0100	.0100 - .0130	.0130 - .0153	.0153 - .0160
	7				Quenched and Tempered	930								275							
	8					1000								300							
	9					1200								350							
	10	High alloyed steel, cast steel, and tool steel			Annealed	680	200	275	.0030 - .0050	.0050 - .0075	.0075 - .0100	.0100 - .0130	.0130 - .0153	.0153 - .0160							
	11				Quenched and Tempered	1100	325														
M	12	Stainless steel (410, 416, 420, 440)		Ferritic/ Martensitic	680	200	230	.0023 - .0047	.0047 - .0070	.0070 - .0094	.0094 - .0126	.0126 - .0138	.0138 - .0140								
	13	Stainless steel (15-5, 17-4)		Martensitic	820	240															
	14	Stainless steel (302, 303, 304)		Austenitic	600	180								.0020 - .0040							
		Stainless steel (310, 316, 321)																			
	14	Stainless steel (323, 329, F55, 2205)		Austenitic/ Ferritic	820	240	150	.0020 - .0035	.0035 - .0045	.0045 - .0050	.0050 - .0055	.0055 - .0059	.0059 - .0060								
N	21	Aluminum Alloy Forging			<12% Si 1000 - 8000 series		820	.0120 - .0140	.0140 - .0200	.0200 - .0250	.0250 - .0260	.0260 - .0268	.0268 - .0270								
	22																				
	23	Aluminum Alloy Casting			>12% Si 4000 series & Castings		820	.0110 - .0150	.0150 - .0190	.0190 - .0230	.0230 - .0240	.0240 - .0248	.0248 - .0250								
	24																				
	25																				
S	36	Titanium Ti alloys Ti1100, Ti6AL4V				Rm 400	150	.0020 - .0030	.0030 - .0040	.0040 - .0050	.0050 - .0065	.0065 - .0084	.0080 - .0084								
	37					Rm1050															

Note: Feed and speed recommendations are starting operating parameters. They are only guidelines from which further optimization should take place. Operating parameters are influenced by many machining variables. These variables may cause for reductions in feeds and speed or dramatic increases. Additionally, DOC and WOC may need to be revised to optimize the tools performance.